

OXY 2 PULSE-OXIMETER

• 35072 OXY 2 PULSE OXIMETER

Pulse Oximeter for measuring pulse oxygen saturation and pulse rate through finger.

Suitable for domiciliar and professional use in family, hospital, oxygen bar, community healthcare, physical care in sports. It can be used before or after sports, but not recommended throughout.

TECHNICAL SPECIFICATIONS

Display mode: LED display
 SpO₂ measuring range: 0 - 100%, (resolution 1%)
 Accuracy: 70 - 100%: ± 2%, below 70% unspecified
 PR measuring range: 30 - 250 bpm, (resolution 1 bpm)
 Accuracy: ± 2 bpm or ± 2% (select larger)
 Measurement performance in weak filling condition: SpO₂ and pulse rate can be shown correctly when pulse-filling ratio is 0.4%. SpO₂ error is ± 4%, pulse rate error is ± 2 bpm or ± 2% (select larger)
 Power consumption: less than 25 mA
 Voltage: DC 2.6 V - 3.6 V
 Battery working hour: two batteries can work continually for 24 hours
 Safety Type: Interior Battery, BF Type
 Dimension - weight: 60x30.5x32.5 mm - 50 g including two batteries

- SpO₂ value display
- pulse rate value display, bar graph display
- low-voltage indicator
- automatical power off the unit will automatically switch off within 5 seconds if the finger falls out of probe



35072

ASPEED 3.0 PROFESSIONAL SINGLE PUMP ASPIRATOR

• 28279 ASPEED 3.0 ASPIRATOR 15 l/min

Portable, compact reliable aspirator ideal for small surgery.

Piston type continuous cycle electric medical device.

High vacuum low flow. It requires no maintenance or lubrication. Made in Italy.

STANDARD ACCESSORIES

Autoclavable polycarbonate jar 1,000 cc with safety valve (overflow protection)
 Disposable suction liner 1 l
 99% Antibacterial hydrophobic filter
 Sterile disposable cannula
 Sterile manual flow regulator
 Set of atoxic sterilizable silicone tubes
 Power Cable
 User Manual GB, FR, IT, DE, ES

TECHNICAL SPECIFICATIONS

Operating voltage: 230 V - 50 Hz
 Power consumption: max 140 VA
 Bottle capacity: 1 l
 High vacuum: low flow
 Air flow: 15 l/min
 Adjustable vacuum level: 0 ÷ -0.85 bar (0 ÷ -85 kPa)
 Size: 300x170x160 mm
 Weight: 2.5 kg
 Noise level: 60 dBA
 Operating cycle: continuously
 Class - Type: II - BF



28279

GIMA code	ACCESSORIES AND SPARES FOR ASPEED
28255	Hydrophobic 99% bacterial filter
28258	Autoclavable jar 1l with cover
28259	Disposable suction liner
25480	Silicone tube 6x12 mm - roll of 30 m
28254	Adaptor to connect catheter to silicone tube

VEGA PLUS PROFESSIONAL SUCTION ASPIRATOR

• 28170 VEGA PLUS SUCTION ASPIRATOR 40 l/min

Professional aspirator for hospital use: tracheotomy, small surgery and post-operative treatments. Silent, high-flow and maintenance-free pump allow long product life and durability. Recommended for nasal aspiration, oral aspiration, tracheal aspiration of body liquids (mucus, catarrh or blood) in adults or children. For use with 1 or 2 jars. Made in Italy.

STANDARD ACCESSORIES

Autoclavable jar (1 l) with overflow valve system
 Antibacterial and hydrophobic filter
 Set of silicone tubes 6x10 mm
 Suction catheter CH20
 Conical connector for probes
 Power cable (Schuko)
 5 languages user manual (GB, FR, IT, DE, ES)



28170 + 28171 + 28226



28170

GIMA code	ACCESSORIES AND SPARES FOR VEGA PLUS
28229	Hydrophobic, 99% antibacterial filter
28226	121°C autoclavable jar 1 l with cover and overflow system
28227	Cover and overflow valve system for 28226
28185	134°C autoclavable jar 1 l with cover and overflow system
28184	Cover and overflow valve system for 28185
28271	Disposable liner 1 l (cover + bag)
28270	Container for disposable liner 1 l
28171	Holder for second autoclavable jar (28226)
28172	Holder for disposable liner (28271)

TECHNICAL SPECIFICATIONS	
Operating voltage:	220-230 V - 50/60 Hz
Power consumption:	max 110 VA
Bottle capacity:	1 l
Air flow:	40 l/min
Max suction:	- 0.80 bar
Size:	
Weight:	3.6 kg
Operating cycle:	continuous
Class - Type:	II - BF