

WristOx₂TM, Model 3150

Wrist-worn Pulse Oximeter



The Most Versatile Wrist-worn Pulse Oximeter for Unmatched Performance and Value!

Engineered with Nonin Medical's proven PureSAT® SpO₂ technology, the WristOx₂TM, Model 3150 delivers highly accurate readings in the widest range of patient populations and settings. From the hospital to the home, the WristOx₂TM, Model 3150 is ideal for applications including ambulatory monitoring, remote wireless monitoring and overnight studies—providing the versatility and reliability that clinicians expect from Nonin. The most advanced wrist-worn pulse oximeter available, the WristOx₂TM, Model 3150 features advanced performance and reporting capabilities, including enhanced connectivity and increased memory storage. A new ergonomic design and Bluetooth® wireless technology eliminate the inconvenience of bulky cables and provide patients with increased comfort and independence—making this pulse oximeter ideal for ambulatory monitoring.

WristOx₂TM, Model 3150

Product Highlights

- **Easy to Use** – Simply put your finger in the sensor
- **Design Updates** – Small size wears like a watch with large display screen and enhanced sensor connector design
- **Software Support** – Advanced features such as 6 Minute Walk Test (6MWT) or overnight sleep reporting available when used with nVISION® data management software
- **Convenient Data Transfer** – Transfer data securely to nVISION® via Bluetooth wireless or USB connection
- **New Sensor Line** – The new WristOx₂ sensors are exclusively designed for use with the new WristOx₂TM, Model 3150



Added Benefits

Versatility – The WristOx₂TM, Model 3150 is an ideal choice for multiple applications where small, portable oximetry is needed

Powerful Battery – 48 hours of battery life (non-Bluetooth), 24 hours with continuous Bluetooth using two AAA alkaline batteries

Enhanced Memory – 1,080 hours of non-volatile memory at a four-second sampling rate with additional high resolution variable sampling options of one or two seconds

Nonin Quality and Support – Rugged durability and industry-leading 3-year warranty

Proven PureSAT® Pulse Oximetry Technology – Fast and accurate response for capturing events in challenging conditions such as motion and low perfusion

Select Your Options

- 8000J-WO2 Adult Flex Sensor, 8000AA-WO2 Clip Sensor, 8000SS-WO2, 8000SM-WO2 and 8000SL-WO2 (small, medium, large) Soft Sensors
- 3150WB - Wristbands available in 6", 8", 10" and 13" lengths.
- 3150I - Adapter cable (for compatibility with all Nonin PureLight® sensors)
- nVISION data management software
- 3150SC - PC USB interface cable
- WristOxCC - WristOx₂ carrying case



Available in Two Configurations

WristOx₂ (3150) Single unit or Starter Kit (3150SK) value bundle with nVISION software, PC USB interface cable and extra wrist straps. System comes with a 8000SM-WO2 Sensor.


Specifications

Dimensions (without sensor or strap)56 mm (2.2") wide x 74 mm (2.91") high x 20 mm (.79") thick
Weight (with batteries and wrist strap)71 grams (2.5 oz)
Warranty3 years
Oxygen Saturation Range (%SpO ₂)0% to 100%
Pulse Rate Range18 to 321 pulses per minute
Displays	
Numeric Displays3-digit Indicators
Pulse IndicatorPulse Strength Bar graph
Accuracy	
Blood Oxygen Saturation (%SpO ₂ ±1 A _{nm}) [*]70 - 100%
Non-motion± 2 digits ^{***}
Low perfusion± 2 digits ^{***}
Motion± 3 digits ^{****}
Pulse Rate (in all 3 listed above)± 3 digits ^{****}
Temperature	
Operating+23° to +104°F (-5° to +40°C)
Storage/Transportation-40° to +158°F (-40° to +70°C)
Humidity	
Operating10% to 95% noncondensing
Storage/Transportation10% to 95% noncondensing
Altitude	
Operating AltitudeUp to 40,000 feet (12,192 meters)
Hyperbaric PressureUp to 4 atmospheres
Power RequirementsTwo 1.5V alkaline AAA batteries
Battery Life	
Operating without Bluetooth®48 Hours Minimum
Operating with Bluetooth®**24 Hours Minimum
Storage9 months
Memory	
TypeNonvolatile
CapacityUp to 1,080 hours @ 4 sec. data storage rate Up to 540 hours @ 2 sec. data storage rate Up to 270 hours @ 1 sec. data storage rate
Classifications per IEC 60601-1/UL60601-1	
Type of ProtectionInternally powered (on battery power)
Degree of ProtectionType BF-Applied Part
Mode of OperationContinuous

^{*} ± A_{nm} encompasses approximately 68% of the population.
^{**} Based on class 2 operation for 23 hours and class 1 operation for 1 hour in a 24 hour period.
^{***} Refer to the operator's manual for additional accuracy specifications.
^{****} As tested with Soft Sensor Series.
 Quality systems registered to ISO 13485:2003

Specifications are subject to change without notice.

Authorized Distributor:



Nonin Medical, Inc.
 13700 1st Avenue North
 Plymouth, MN ■ 55441-5443 ■ USA
P +1.763.553.9968 **TF** 800.356.8874
F +1.763.577.5521 **E** info@nonin.com

Nonin Medical AB
 Fibervägen 2, 82450
 Hudiksvall, Sweden
P +46 650 401500
F +46 650 401514
E infointl@nonin.se

www.nonin.com

