

## TREATMENT CHAIR - FLOW

### Summary

<b>Series</b>	Flow
<b>Description</b>	Treatment chair
<b>Code</b>	PFL01
<b>Dimensions</b>	mm. 1960x920x600/920H
<b>RDM</b>	1697614
<b>CND</b>	V0802

### Description

**Configuration:**  
height adjustable therapy chair with 4 moving electric motors, adjustable backrest and legrest, adjustable armrest, push handle, with roll holder.

**STRUCTURE:**  
made of tubular steel, with washable and easy to disinfect thermoformed carter to protect mechanic parts. Basement complete with 100 mm diameter twin wheels independent brake.

#### LYING SURFACE:

Lying surface divided into three electrically adjustable sections. The optimal adaptation to the patient's body is obtained thanks to shaped and foam padding with a thickness of 120 mm. Upholstered in fire retardant and washable imitation leather.

#### ARMRESTS:

Large removable padded armrests, upholstered in fire retardant imitation leather.

- height adjustable;
  - laterally adjustable;
  - retractable to allow an easy access for the patient
- Provided with an automatic system that adjust the armrest's tiltin while the backrest adjustment

#### FINISH:

thermosetting epoxy powder coating with an antibacterial additive.



## TREATMENT CHAIR - FLOW

### Summary

<b>Series</b>	Flow
<b>Description</b>	Treatment chair
<b>Code</b>	PFL01
<b>Dimensions</b>	mm. 1960x920x600/920H
<b>RDM</b>	1697614
<b>CND</b>	V0802

### Movements

Treatment chair with handset control for operator's use with 12 button and 8 functions:

- 2 keys for backrest adjustment
- 2 keys legest adjustment
- 2 keys height adjustment
- 2 keys Trendelenburg and Reverse-Trendelenburg adjustment
- 1 key for patient descent position \*\*\*
- 1 key for sitting position regulation \*\*\*
- 1 key for examination couch position \*\*\*
- 1 key CPR Schock position \*\*\*

\*\*\* *synchronized movement*

**SHOCK position:**  
with a dedicated button (red coloured) it is possible to move the chair into "Shock position".  
This adjustment reset the chair's sections and move the chair into Trendelenburg position.

### Technical data

Min. seat height:	mm	600
Max. seat height:	mm	920
Backrest adjustment:	°	0° - 80°
Tight section adjustment:	°	-90° - 0°
Trendelenburg adjustment:	°	0° - 14°
Seat dimensions:	mm	540x480
Overall dimensions:	mm	1960x920
Protection class:	IP	66
Safe working load	kg	210

### Electical data

Supply Voltage - Network frequency:	-	100-240 V - 50/60Hz
Alimentazione motori:	V	24
Protection Class:	-	II - Tipo B
Socket type:	-	SCHÜKO

### Accessories UPON REQUEST:

- IV pole;
- removable headrest;
- battery.

### Chair CE marked, complies with:

Document N. : 93/42/CEE - Council Directive 93/42/EEC of 14 June 1993 concerning medical devices.